






CHIUSINO SUPERIORE APERTURA
ESTERNA CON OMOLOGAZIONE PED

 Upper manhole with outwardly opening with PED Approval.

 Domdeckel mit aussen Öffnung mit PED.

 Trappe supérieure avec ouverture extérieure avec PED.

 Domo superior con apertura exterior con homologación PED.

• LUCE UTILE DI PASSAGGIO:
300 – 400 – 450 – 500 – 600 – 700 mm
Access: 300 – 400 – 450 – 500 – 600 – 700 mm

• PRESSIONE MASSIMA DI ESERCIZIO:
VEDI TABELLA PAG. 93-94
Max working pressure: : Check the data in the chart p. 93-94

• TEMPERATURA: -20°C /+ VEDI TABELLA
PAG. 93-94
Working temperature: -20/+ Check the data in the chart p. 93-94

• MATERIALE:
AISI 304(W.NR.1.4301) - AISI 316/L
(W.NR.1.4404)
**Material: stainless steel AISI 304
(W.NR.1.4301) - AISI 316/L(W.NR.1.4404)**

• VOLANTINO DI SERIE:
VOLANTINO INOX (VLT1609003S)
**Standard handwheel: stainless steel
handwheel (VLT1609003S)**

• GUARNIZIONE DI SERIE:
SILICONE FINO A 200°C
Standard gasket: silicone up to 200°

• FINITURA SUPERFICIALE DI SERIE:
COPERTURA SATINATO/TELAIO
SATINATO
Standard finish: satin cover/ satin frame

• SU RICHIESTA: SPIE VISIVE MAX DN 125
On request: sight glasses max DN 125

