

A	200	300	420	460	500	600
B	2,5	2,5	2,0	2,0	2,0	2,0
C	2,0	2,0	1,5	1,5	1,5	2,0
PRESSIONE PRESSURE	-0,3/0,01 Bar	-0,3/0,01 Bar	-0,3/0,01 Bar	0 Bar	0 Bar	0 Bar

CHIUSINO SUPERIORE APERTURA
ESTERNA GIREVOLE.



Upper manhole with swiveling
outwardly opening.



Domdeckel mit schwenkbar aussen
Öffnung.



Trappe supérieure avec ouverture
extérieure pivotante.



Domo superior con apertura exterior
pivotante.



- LUCE UTILE DI PASSAGGIO:
200 – 300 – 420 – 460 – 500 – 600
mm

**Access: 200 – 300 – 420 – 460 – 500 –
600 mm**

- PRESSIONE MASSIMA DI ESERCIZIO:
VEDI DATI IN TABELLA

**Max working pressure:
Check the date in the chart**

- MATERIALE:
AISI 304(W.NR.1.4301) - AISI 316/L
(W.NR.1.4404)

**Material: stainless steel AISI 304
(W.NR.1.4301) - AISI 316/L(W.NR.1.4404)**

- VOLANTINO DI SERIE:
VOLANTINO IN NYLON (VLT1207004)

**Standard handwheel: nylon handwheel
(VLT1207004)**

- GUARNIZIONE DI SERIE:
GOMMA NATURALE (PARA)

Standard gasket: natural rubber

- FINITURA SUPERFICIALE DI SERIE:
COPERTURA LUCIDATURA ECONOMICA/
TELAIO 2B

**Standard finish: economic polished
cover/2B frame**

