

A	200	300	420	460	500	600
B	2	2	2.5	2.5	2.5	2.5
C	35X8	35X8	40X10	40X10	40X10	40X10
D	320	425	560	560	640	740
PRESSIONE PRESSURE	-0,5/+0,2 Bar	-0,5/+0,2 Bar	-0,5/+0,2 Bar	-0,5/+0,2 Bar	-0,5/+0,05 Bar	-0,5/+0,05 Bar

CHIUSINO SUPERIORE APERTURA
ESTERNA GIREVOLE.



Upper manhole with swiveling
outwardly opening.



Domdeckel mit schwenkbar aussen
Öffnung.



Trappe supérieure avec ouverture
extérieure pivotante.



Domo superior con apertura exterior
pivotante.

- LUCE UTILE DI PASSAGGIO:
200 – 300 – 420 – 460 – 500 – 600 mm
Access: 200 – 300 – 420 – 460 – 500 – 600 mm

- PRESSIONE MASSIMA DI ESERCIZIO:
VEDI DATI IN TABELLE

Max working pressure:
Check the date in the chart

- MATERIALE:
AISI 304(W.NR.1.4301) - AISI 316/L
(W.NR.1.4404)
**Material: stainless steel AISI 304
(W.NR.1.4301) - AISI 316/L(W.NR.1.4404)**

- VOLANTINO DI SERIE:
VOLANTINO NYLON (VLT1207004)
**Standard handwheel: nylon handwheel
(VLT1207004)**

- GUARNIZIONE DI SERIE:
GOMMA NATURALE (PARA)
Standard gasket: natural rubber

- FINITURA SUPERFICIALE DI SERIE:
COPERCHIO LUCIDO/TELAIO LUCIDO
**Standard finish: polished cover/polished
frame**

